

**SOURCEWELL CONTRACT NO. 122017-GPV**



---

**PREPARED BY**

Plumber's Depot

Jose Martin - jose.martin@plumbersdepotinc.com

---

**PREPARED FOR**

Rodolfo Hurtado

City of Manhattan Beach  
3621 Bell Ave  
Manhattan Beach, CA 90266

# QUOTE

**GapVax**®



**QUOTE ID**

**2120-012 01-10-2022**

**UPDATED:**

**9/15/2021**



## 2023 MC1005-3S3S COMBINATION JET/VAC

QUOTE ID: 2120-012 01-10-2022

January 10, 2022

NOTE: THE GAPVAX MC UNIT MAY EXCEED FEDERAL BRIDGE ALLOWABLE WEIGHTS WHEN LOADED WITH WATER, OR DEBRIS, AND/OR BOTH WATER AND DEBRIS COMBINED. PLEASE CONSULT FACTORY.

	OPTION DESCRIPTION	NOTES	QTY
CHA001	PETERBILT 548 4 X 2 - 360 HP - 50,000 LB. GVWR - AUTO	MODEL YEAR 2023	1
	WHITE CAB COLOR		1
	STOCK CHASSIS ARE SUBJECT TO PRIOR SALE, LIMITED QUANTITY ARE AVAILABLE		1
STD	5 USABLE YARD DEBRIS TANK MADE OF 3/16" ASTM A-572 GRADE 50 EXTEN STEEL		STANDARD
STD	FULL-OPENING REAR TAILGATE		STANDARD
STD	STAINLESS STEEL TAILGATE SEALING ROD		STANDARD
STD	FOUR HYDRAULIC REAR DOOR LOCKS		STANDARD
STD	DUAL TAILGATE LIFT CYLINDERS		STANDARD
STD	FRONT MOUNTED HOIST CYLINDER, POWER UP AND DOWN, 55,000 LB CAPACITY		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF BODY		STANDARD
STD	FIVE YEAR WARRANTY ON DEBRIS TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS		STANDARD
STD	THREE TIE-OFF ANCHORS ON TOP OF THE BODY 6' APART		STANDARD
A1B	STAINLESS DEBRIS BODY FLUSH OUT SYSTEM		1
A2B	DRAIN AT BOTTOM OF TAILGATE - 6" BUTTERFLY VALVE WITH 15' OF LAYFLAT HOSE	VALVE IS NOT REPAIRABLE	1
A3-CS	FLOAT TYPE LIQUID LEVEL INDICATOR ON SIDE OF DEBRIS TANK		1
A5	TRASH PUMP - STANLEY 3" 450 GPM WITH LAY-FLAT HOSE AND CAM-LOC FITTINGS	NOT RECOMMENDED FOR CONTINUOUS USE	1
A11A	FILTER SCREEN FOR DRAIN VALVE (SHORT BOX)	REQUIRES A2	1
A17	UPGRADE TO STAINLESS STEEL DEBRIS TANK		1
A21	CURBSIDE LADDER TO PORT INSPECTION AREA		1
A18	PURGE VALVE AT GRAVITY DRAIN (1-1/4" BALL VALVE)		1
A34B	UPGRADE DEBRIS BODY BAFFLE TO STAINLESS STEEL		1
STD	1000 GALLON WATER TANK MADE OF 3/16" 304 STAINLESS STEEL		STANDARD
STD	4" HIGH ANTI-SIPHON RING WITH (4) 2-1/2" HOLES		STANDARD
STD	WATER TANK LEVEL SIGHT TUBE ON CURBSIDE		STANDARD
STD	DRAIN VALVE AT BOTTOM OF WATER TANK		STANDARD
STD	3" FILL LINE WITH 2-1/2" FIRE HOSE CONNECTION CURBSIDE		STANDARD
STD	3" WATER STRAINER WITH STAINLESS STEEL SCREEN ON WATER TANK FILL LINE		STANDARD
STD	3" SUPPLY LINE TO WATER PUMP MOUNTED AT REAR HINGE PIN		STANDARD
STD	FIVE YEAR WARRANTY ON WATER TANK AGAINST RUST THROUGH, DISTORTION AND CRACKS		STANDARD
B3	TANK INTER-CONNECT WITH DEBRIS TANK	REQUIRES A2, B10	1
B10	ADDITIONAL 3" FILTER BETWEEN WATER TANK AND PUMP (3" Y-STRAINER)		1
B23B	STAINLESS BAFFLES IN THE WATER TANK		1

<b>B30</b>	UPGRADE TO BUTTERFLY VALVE IN 3" SUPPLY LINE	STANDARD
STD	TRUE 8" DIAMETER VACUUM SYSTEM	STANDARD
STD	VACUUM PUMP DRIVEN VIA MID-SHIP MOUNTED SPLIT SHAFT TRANSFER CASE GEARBOX (PTO)	STANDARD
STD	NOISE & VIBRATION DAMPENING MOUNTS ON VACUUM PUMP AND TRANSFER CASE	STANDARD
STD	NOISE ATTENUATED VACUUM PUMP DISCHARGE SILENCER WITH RAIN CAP AND DRAIN	STANDARD
STD	24" CENTRIFUGAL CYCLONE SEPARATOR WITH 20" CHAMBER	STANDARD
STD	DUAL STAINLESS STEEL SHUTOFF FLOAT BALLS MOUNTED AT THE REAR OF DEBRIS TANK	STANDARD
STD	STAINLESS STEEL VEE-WIRE SAFETY SCREEN	STANDARD
STD	6" SAFETY VACUUM RELIEF	STANDARD
STD	PANIC SWITCH FUNCTION FOR VACUUM	STANDARD
C8	UPGRADE TO ROOTS TYPE VACUUM PUMP 4,500 CFM AND 18" HG (4) 18" Hg VACUUM RELIEF VALVES	1
STD	TRI-PLEX WATER PUMP SYSTEM	STANDARD
STD	800 PSI WASHDOWN CIRCUIT WITH 50' X 1/2" HOSE	STANDARD
STD	AIR PURGE SYSTEM FOR PRIMARY CIRCUIT	STANDARD
STD	LOW POINT DRAIN VALVES ON WATER LINES	STANDARD
STD	SET WASHDOWN CIRCUIT TO FULL WORKING PRESSURE	OPTION D4 IS RECOMMENDED 1
D5A	GIANT GP8000 SERIES WATER PUMP RATED AT 63 GPM @ 3000 PSI	1
<b>D7A</b>	50' X 1/2" HAND GUN REEL FOR WASHDOWN CIRCUIT	1
STD	8" FRONT MOUNTED TELESCOPING BOOM WITH 26' REACH AND 180 DEG. ROTATION	STANDARD
STD	180 DEGREE POWER ROTATION VIA WORM DRIVE	STANDARD
STD	DUAL 4" LIFT CYLINDERS	STANDARD
STD	CAB PROTECTION RACK	STANDARD
<b>E6</b>	REMOTE LUBE FOR BOOM LIFT AND ROTATION	1
STD	FRONT FRAME MOUNTED HOSE REEL WITH 180 DEGREE ARTICULATION	STANDARD
STD	HOSE REEL RATED FOR 800' OF HOSE AND 3,000 PSI	STANDARD
STD	EXTERIOR HOSE EXPANSION RIBS	STANDARD
<b>F1A</b>	FOOTAGE COUNTER ON SIDE OF SPOOL	1
F6	UPGRADE FRONT HOSE REEL TO POWER ARTICULATE VIA HYDRAULICS	1
<b>F11</b>	AUTOMATIC HOSE LEVEL WINDER (INCLUDES "J-HOOK" STLYE HOSE GUIDE)	1
STD	CAB-MOUNTED AIR SHIFT CONTROLS FOR BLOWER, HYDRAULICS, AND WATER PUMP	STANDARD
STD	CONTROL PANEL MOUNTED AT FRONT HOSE REEL	STANDARD
STD	OPERATOR CONTROL PANEL INCLUDES GUAGES FOR ENGINE, HYDRAULICS, VACUUM, AND WATER PUMP	STANDARD
STD	PANIC SWITCH TO RELIEVE WATER PRESSURE AND VACUUM	STANDARD
STD	30' PENDANT REMOTE WITH BOOM FUNCTIONS	STANDARD
G2C	<b>G2C</b> CONTROL SYSTEM WITH DP700 DISPLAY INCLUDES:	1
	LOW WATER SHUTDOWN PROTECTION	1
	HIGH WATER TEMPERATURE SHUTDOWN PROTECTION	1
	ENGINE OVERSPEED PROTECTION	1
	ON-SCREEN DIAGNOSTICS FOR WATER, PTO AND ENGINE LEVELS	1
	TEMPERATURE AND PRESSURE LEVELS FOR VACUUM, WATER, HYDRAULICS	1
	PROVISION FOR INCLUDING DIGITAL FOOTAGE COUNTER ON SCREEN F1C NOT INCLUDED	1

G4	HIGH DEBRIS LEVEL LIGHT & ALARM	REQUIRES A3	1
G5	BLOWER TEMPERATURE GUAGE		1
	OMNEX T110 WIRELESS REMOTE		STANDARD
G19	WIRELESS REMOTE WITH BOOM AND VACUUM FUNCTIONS		1
STD	TRUCK-LITE LED RUNNING (MARKER) LIGHTS		STANDARD
STD	LED STOP/TAIL/TURN LIGHT WITH POLISHED STAINLESS STEEL BOXES		STANDARD
H5C	(2) BOOM WORK LIGHTS - HIGH INTENSITY HELLA PB1500 LED WORK LIGHTS (PN: LHT022406)	POWER BEAM / SPOT LIGHT (RATED 1300 LUMEN EACH)	1
H6B	(2) REAR WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429)		1
H7BA	(2) SIDE WORK LIGHTS - HELLA LED WORK LIGHTS (PN: LHT022429) (1 PER SIDE)		1
H19D	CODE 3 REAR SUPER LED FLASHERS - 6 LIGHT HEADS		1
	3 ON EACH SIDE REAR (1 @ 45 DEGREES)		1
H33	REAR ARROW LIGHT - LOW PROFILE LED (CA TITLE-13 COMPLIANT) TRAFFIC ADVISOR	(LHT022544, CODE 3 TORUS NARROWSTIK OR EQUAL)	1
H39B	TWO HIGH INTENSITY LED WORK LIGHTS (HELLA PB1500) ON FRONT HOSE REEL TO SHINE INTO MANHOLE		1
STD	25' FIRE HOSE BASKET		STANDARD
I6F-CS	STAINLESS STEEL, 36" WIDE X 24" TALL X 24" DEEP, MOUNTED ON THE CURBSIDE		1
I7C-DS	36" TOOL BOX - STAINLESS STEEL, 36" WIDE X 24" HIGH X 24" DEEP, MOUNTED ON THE DRIVER'S SIDE		1
I14	TRAFFIC CONE HOLDER ON DRIVER'S SIDE		1
I22	UPGRADE TUBE TRAYS TO POLISHED STAINLESS STEEL		1
I26C	TWO BUMPER TOOL BOXES - STAINLESS STEEL, 16" HIGH X 12" WIDE X 18" DEEP WITH FOLD DOWN DOOR		1
STD	DOT LIGHTING / FENDERS / MUD FLAPS / TAILGATE SAFETY PROP, ICC LIGHTS		STANDARD
STD	REMOTE ACTUATED BODY SAFETY PROP		STANDARD
STD	70 GALLONS AW-46 HYDRAULIC OIL, LEVEL/TEMPERATURE GAUGE, SHUTOFF ON SUCTION		STANDARD
STD	REAR BUMPER, TRIANGLE KIT, FIRE EXTINGUISHER, BACKUP ALARM		STANDARD
STD	ALLISON 10-BOLT PTO UPGRADE		STANDARD
J0B	FRONT BUMPER - CALIFORNA FRONT BUMPER		1
STD	PAINTED WITH PPG URETHANE PAINT		STANDARD
STD	PAINT BODY WHITE		STANDARD
STD	PAINT FRAME AND PARTS BLACK		STANDARD
STD	PAINT HOSE REEL AND BOOM BLACK		STANDARD
STD	FLEET FINISH		STANDARD
STD	25 FEET OF VACUUM TUBING (5) AND CLAMPS		STANDARD
STD	TIGER TAIL HOSE GUIDE		STANDARD
STD	TWO BLUE STAR SEWER CLEANING NOZZLES		STANDARD
M3	FILL HOSE 25' X 2 1/2"		1
M5B	LEADER HOSE 10' X 3/4"		1
M9I	3/4" PIRANHA SEWER HOSE - 3,000 PSI X 800 FT PLASTIC (BLUE) (PN: HOS022499)		1
M29B	TWO CAMERA - BACK-UP CAMERA SYSTEM WITH 7" COLOR MONITOR (RV-505A), INCLUDES DVR-916 REAR AND DVR-921 FRONT CAMERA		1



## PRICING SUMMARY

<b>PRICE OF BASE UNIT WITH OPTIONS:</b>		<b>\$ 458,460.08</b>
<b>DELIVERY:</b> (\$1,000.00 MINIMUM)	<b>@ \$3.00 PER MILE</b>	<b>\$ 6,500.00</b>
<b>ESTIMATED SUBTOTAL:</b>		<b>\$ 462,960.08</b>
<b>SALES TAX:</b>		<b>\$ 43,363.71</b>
<b>TOTAL PRICE (PER UNIT):</b>		<b>\$ 506,323.79</b>

DUE TO EXTREME MARKET VOLATILITY AND PENDING U.S. GOVERNMENT SECTION 232 TRADE CASES ALL PRICES AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE, ALL QUOTES TO BE CONFIRMED AT TIME OF ORDER

**\*\*\* FOB DESTINATION \*\*\***

SIGNATURE

DATE

Please return a signed copy to [jose.martin@plumbersdepotinc.com](mailto:jose.martin@plumbersdepotinc.com)

**QUOTE ID**  
**2120-012 01-10-2022**

**LAST UPDATED:**  
**9/15/2021**

# GapVax Incorporated

## Terms and Conditions of Sale

1. **ORDERS.** All orders are subject to acceptance by an officer of GapVax Inc. Orders for products not regularly carried in stock or requiring special engineering or manufacture are in every case subject to approval by an officer of GapVax.
2. **PERFORMANCE.** GapVax Inc. shall not be liable for failure to complete the contract in accordance with its terms if failure is due to wars, strikes, fires, floods, accidents, delays in transportation or other causes beyond its reasonable control.
3. **EXPERIMENTAL WORK.** Work performed at customer's request such as sketches, drawings, design, testing, fabrication and materials shall be charged at current rates.
4. **SKETCHES, ENGINEERING DRAWINGS, MODELS** and all preparatory work created or furnished by GapVax Inc. shall remain its exclusive property; and no use of same shall be made, nor may ideas obtained therefrom be used, except with the consent of and on terms acceptable to GapVax Inc.
5. **CANCELLATION.** Orders regularly entered cannot be canceled except upon terms that will compensate GapVax Inc. for any loss or damage sustained.
6. **SHIPMENT.** All proposals are based on continuous and uninterrupted delivery of the order upon completion, unless specifications distinctly state otherwise. In the event that agreement is reached for GapVax Inc. to store completed items, they will be immediately invoiced to the customer and become due and payable. Storage shall be at the risk of the customer and GapVax Inc. shall be liable only for ordinary care of the property.
7. **CUSTOMER'S PROPERTY.** GapVax Inc. shall charge the customer at current rates, for handling and storing customer's property (e.g. truck chassis) held for more than thirty (30) days after notification of availability for shipment. All customer's property, or third party's property, that is stored by GapVax Inc. is at the customer's or other party's risk. GapVax is not liable for any loss or damage thereto caused by fire, water, corrosion, theft, negligence, or any cause beyond its reasonable control.
8. **PRICES.** All orders are subject to current prices in effect at the time of order acknowledgment.
9. **F.O.B. POINT.** Unless otherwise stated, all prices listed are F.O.B. point of manufacture.
10. **TAXES.** Unless specifically stated, prices listed do not include Federal, State, City or other excise occupation, sales, use or similar taxes which are extra and are to be added at rates in effect at time of shipment. If federal Excise Taxes are included or listed on the reverse side of this paper, they are stated at the rates and regulations in effect at the time this order is written, and are subject to revision in accordance with rates and regulations in effect at time of shipment.
11. **PRODUCT IMPROVEMENT.** GapVax Inc. reserves the right to change manufacturing specifications and procedures without incurring any responsibility for modifying previously shipped products.
12. **MOUNTING PRICES.** Mounting prices assumes normal factory installation on a truck chassis suitable for the unit purchased. Relocation of batteries, gas tanks, mufflers, air tanks, etc. will be an additional charge, billed at the standard factory labor rate.
13. **WARRANTY.** GapVax Inc. warrants its products to be free from defects in material and workmanship, subject to the limitations and conditions set forth in its current published warranty but makes no warranty of merchantability or fitness for any particular purpose. GapVax Inc. does not assume liability for any loss of product, time or any direct, indirect, or consequential damage, losses or delay or any nature whatsoever. No warranty, express or implied, is made or authorized to be made and no obligation is assumed or authorized to be assumed with respect to products of GapVax Inc. other than that set forth in the current, published warranty. It is to be understood that the acceptance this order is expressly conditioned upon your acceptance of GapVax Inc. standard written warranty for the products sold hereunder GapVax Inc. hereby disclaims any responsibility or liability for any consequential losses delays or downtime resulting from orders hereunder the use of its products. GapVax does not and will not warranty any tank coating or tank lining. PTO damage is not covered when the PTO protection system or low water shut down system is not selected / installed / and operational.
14. This agreement shall be construed according to the laws of the State of Pennsylvania. Our failure at anytime to exercise any right we may have under the agreement shall not constitute a waiver thereof nor prejudice our right to enforce same thereafter.
15. This order, including the above terms and conditions contains the complete and final agreement between the parties hereto and no other agreement in any way modifying any of said terms and conditions will be binding on us unless in writing and agreed to by authorized representative of this company.